



- NOTES:

- SITE PLAN**
- SCALE: 1"=20'
- N
- 

SCALE: 1"=20'

- | | |
|---------------------------------|---|
| TYPE 42 CONCRETE CURB | INSTALL TOPSOIL, MULCH, D. SAWN, R. I/C |
| CONCRETE SIDEWALK | R. I/C, CURB IN 2' OR MATCH EXISTING CURB |
| SEWAL CURB RAMP | INSTALL "NO PARKING" SIGN, MULCH, D. SAWN, R. I/C |
| STANDARD GUTY ASPHALT | |
| EXTORIOR CONCRETE SLAB ON GRADE | |
| NO PARKING STALL | EDGE OF PAVEMENT |
| HANDICAPPED PARKING MARKINGS | UNPAVED AREA, SEE LANDSCAPE PLAN FOR PLANTINGS, INSTALL TOPSOIL & SEED |
| HANDICAPPED PARKING SIGN | 5' WIDE WALKWAY, 10' X 10' (4' X 4' SPACING CROSSWALK) |
| HANDICAPPED PARKING RAMP | 8" DEEP SIDEWALK, 1.5' X 1.25 M. PROVIDE TACTILE WARNING STRIPS IN ACCORDANCE WITH ADA/CURB |
| LANDSCAPE | PROVIDE CURB OPENING FOR DRAINAGE, SLOPE UP TO 0.5% IN 2' EITHER SIDE |
| MULCHER/STAIN COLORED | |

NOTE LEGEND

1. INSTALL STOP SIGN, MULTID. SIGN NO. R1-C
2. ROUNDOUT CURB IN 2' OR MATCH EXISTING CURB
3. INSTALL 10" NON-PARKING SIGN, MULTID. SIGN NO. B7-C
4. LANDSCAPE AREA, SEE LANDSCAPE PLAN, IF NO PLANTINGS, INSTALL TOP SOIL & SEED
5. EDGE OF PAVEMENT
6. 6" WIDE WHITE PAVEMENT STRIPE AT 5' SPACING CROSSWALK
7. SLOPE SIDEWALK @ 1:12 MAX. PROVIDE TACTILE WARNING STRIPE IN ACCORDANCE W/ CODE
8. PROVIDE 2' CURB OPENING FOR DRAINAGE. SLOPE UP TO 6" CURB IN 2' EITHER SIDE


NOTE: BUILDINGS AND PARKING ARE LAYED OUT PARALLEL AND PERPENDICULAR TO THE ONONDAGA STREET AND FAIRCHILD STREET R.O.W.'S

6

PROPOSED LIGHT POLE W/ SIGN

PROPOSED ASPHALT PAVEMENT

PROPOSED ASPHALT PAVEMENT



PROJECT NAME:

New Construction
Housing D
765 Fairchild Pl
Lewiston, New York


Issued for Construction: xx.xx.xx
Municipality Submission: 3/4/16
Drawn by: C. Wood
Scale: As Noted

DRAWING NAME:

Site Plan

DRAWING NO.

Project no.: 14.xxx



**Carmina
Wood
Morris^{PC}**

487 Main Street, Suite 600
Buffalo, New York 14203
P 716.842.3165
F 716.842.0263